

NOVENTA 3.5 RECESSED TRIMLESS NV3.5R

Gyp. Board Installation Guide



IMPORTANT SAFETY INSTRUCTIONS

When installing or using this suspended fixture basic safety precautions should be followed

Read ALL INSTRUCTIONS before installing fixture.

- This fixture is intended for installation in accordance with the National Electric Code and Local and State Codes and must be installed by a licensed electrical contractor.
- THIS FIXTURE IS FOR INSTALLATION IN NON-INSULATED WALLS OR CEILINGS ONLY
- DANGER - RISK OF SHOCK AND FIRE - DISCONNECT POWER BEFORE INSTALLATION

SAVE THESE INSTRUCTIONS

Tel: (510) 489-2530 Fax: (650) 2490412 web: www.alwusa.com

NOVENTA 3.5 RECESSED TRIMLESS NV3.5R

Gyp. Board Installation Guide



NOTICE:

For proper installation, have a qualified electrician install this product. Before installation of any luminary onto an electrical junction box, be sure to disconnect power. This luminary must be wired and grounded in accordance with the National Electrical Code, local codes, and ordinances. Wire supply connections must be made with U.L. or ETL approved connectors. Check that luminary voltage and building voltage are the same.

CAUTION:

EXERCISE SPECIAL CARE AND SAFETY WHILE INSTALLING AND SERVICING LUMINARY. USE OF SOFT GLOVES AND - PADDED MATERIALS ARE RECOMMENDED DURING HANDLING TO AVOID MARRING THE FINISH.

INSTRUCTION:

1. TURN OFF POWER at fuse box before installing fixture.
2. If joining multiple fixtures together, remove LENS and REFLECTOR and loosen the set screws on the JOINER BRACKETS. Connect wires between fixtures using connectors provided (if needed) and push excess wire into fixtures. DO NOT PINCH WIRES BETWEEN THE PARTS. Join sections together and secure joined fixtures with the JOINER BRACKET set screws.
(Maintenance note: Removing LENS and REFLECTOR will allow access to ballasts/drivers)
3. Attach BUILDING POWER using U.L approved wire connectors: Connect the neutral (white) to the supply neutral, connect the line wire (black) to the supply line wire. Fasten ground wire(s) (green) to ground wire.
4. Provide continuous blocking to mount fixture.
5. Apply masking tape to lens for plaster protection.
6. Use fasteners to secure fixture to blocking.
7. Affix Gyp. board to fixture.
8. Tape and feather patching compound over seam, sanding as needed.

